

Swivel

The Peak Swivel is designed to allow free rotation of the toolstring and minimize line torque during slickline or cable deployment.

The Swivel can be positioned at any point along the length of the toolstring depending on the application to suit operational requirements. The Swivel incorporates several design features including an integral grease nipple to ensure internal components are continuously lubricated for a prolonged working and storage period. Critical internal components of the Swivel are also electroless nickel-plated to further assist in prevention of internal corrosion which is common with standard swivel joints.

APPLICATIONS

- Predominantly used to provide rotation in a wireline toolstring and minimize line torque
- The Swivel can be utilized to provide a rotating point when handling long or cumbersome tools to aid make up or break out
- The Swivel can also be positioned directly above manipulation tools ie a kick-over tool, to enable an enhanced rotation at depth

FEATURES AND BENEFITS

- Integral grease nipple to ensure easy lubrication and prevent corrosion
- Critical components ENP treated to further assist in prevention of internal corrosion
- Heavy-duty robust design
- Contingent fish neck on most lower joint components
- Third-party proprietary connections available to suit customer requirements

TECHNICAL INFORMATION

Actual OD, in	Fish Neck, in
1.250	1.187
1.500	1.375
1.750	1.375
1.875	1.750
2.125	1.750
2.500	2.313



Product Code: Swivel / 130

info@peakwellsystems.com | peakwellsystems.com

© 2017 Peak Well Systems Pty Ltd. All rights reserved. Revision: 8th April 2014

