

Heavy-Duty Dual Fish Neck Sub

The Heavy-Duty (HD) Dual Fish Neck Sub is used to provide a secondary heavy-duty fish neck profile in addition to the conventional fish neck profile.

The 45 degree secondary Peak HD Fish Neck has a 60% increased load bearing area compared to standard fish necks. This is designed for use in conjunction with the Peak HD FRC Pulling Tool and can withstand prolonged heavy jarring impact.

APPLICATIONS

- For use as a running and retrieval neck on Wire Grabs, Non-Releaseable Overshots, Non-Releaseable Spears, etc

FEATURES AND BENEFITS

- Peak HD Fish Neck has a 60% increased load bearing area compared to standard fish necks and is designed for use in conjunction with the Peak HD FRC Pulling Tool
- 45 degree profile of the Peak HD Fish Neck assists in tool release after prolonged upward jarring
- 45 degree profile of the Peak HD Fish Neck assists in tool release at high angles in deviated wellbores
- Conventional upper neck profile for use with industry standard running and pulling tools
- Bottom connection supplied to suit customer requirements
- Robust design

TECHNICAL INFORMATION

Actual OD, in	Primary Neck, in	Secondary Neck, in
1.500	1.375	1.437
1.875	1.750	1.812
2.500	2.313	2.375



▲ HD FRC Pulling Tool engaging the Peak HD Dual Fish Neck

Product Code: Heavy-Duty Dual Fish Neck Sub / 123

info@peakwellsystems.com | peakwellsystems.com

© 2017 Peak Well Systems Pty Ltd. All rights reserved.

peak 
WELL SYSTEMS